

# plant growth

## Percival® model E-36L2

Standard SciWhite™ lighting

### applications

- This chamber is frequently used for soybean, rice, tomato, cotton or other short to medium height plants
- Many other applications exist for this product

*Please compare your own requirements to the specifications listed below.*

### IntellusUltra controller

The IntellusUltra control system (C8) was purpose-built for controlled environments and is standard on all Percival chambers.

- Robust and reliable, industrial-grade integrated hardware design
- Highly flexible architecture facilitates configuration, expansion and customization
- Precise, simultaneous control of up to 7 environmental parameters
- Industry-leading experiment protection and system diagnostics

### IntellusUltra control graphical user interface

A touchscreen user interface is provided as standard on all Percival Scientific plant growth chambers and allows users to interact with their controlled environment in new and intuitive ways.

- 10.1" IPS, high resolution display with 10-point multi-touch sensitivity
- Tabular and graphical presentation of chamber programs and parameters
- Highly visible process values and alarm notifications
- Enhanced user feedback menus

*Please refer to [www.percival-scientific.com](http://www.percival-scientific.com) for additional information regarding the control systems.*

### SciWhite LED lighting system

- Two tiers of lighted shelving, lit by SciWhite LEDs with enhanced red
- Intensity programmable up to 680  $\mu\text{moles}/\text{m}^2/\text{s}$  of light irradiance measured @ 6" from LEDs

### E-36L2 specifications (subject to change without notice)

Temp Range with all lights on	Interior Space volume		Total Shelving Floor Area		Maximum Growing Height		Exterior Dimensions						Light Intensity 6" from lamps unless otherwise noted	Tiers
	°C	ft <sup>3</sup>	m <sup>3</sup>	ft <sup>2</sup>	m <sup>2</sup>	in	cm	width		depth		height		
°C	ft <sup>3</sup>	m <sup>3</sup>	ft <sup>2</sup>	m <sup>2</sup>	in	cm	in	cm	in	cm	in	cm	$\mu\text{moles}/\text{m}^2/\text{s}$	
7-44±0.5	29.7	0.8	10.8	1	22.6	57.5	33.5	85.1	33.6	85.4	77.2	196.1	680	2



### SciWhite LED lighting system, continued

- Programming and control of the lighting is done via IntellusUltra real time controller
- Dimmable between 10-100% output

### airflow/circulation

- Air circulation inside chamber is from a specifically designed adjustable air diffuser (conditioned air travels along the entire back wall, over the shelves and returns to the ceiling fans through an opening between the light fixtures and the doors)

### cabinet construction

- Interior constructed of 26-gauge galvanized steel
- Interior floor constructed of 24-gauge polished stainless steel
- Exterior constructed of 24-gauge Galvannealed extra-smooth steel
- NSF-compliant seam design
- Overall wall thickness is 2" (5.1 cm)
- Integrated floor drain
- Contains casters assembly and adjustable leveling legs
- One 1.25" access port with air-tight plug
- Highly durable and reflective coating

# plant growth Percival model E-36L2

## insulation

- Woodless construction using 2" thick foamed-in-place non-CFC Urethane insulation with 97% closed cell-structure density of 2.2 lbs/ft<sup>3</sup>

## door

- One door opening 29.3" x 57.5" (74.3 cm x 146.1 cm) provides full access to the chamber interior
- Magnetic gasket provides a tight seal to door frame
- Lift-off hinge design allows for simple removal of door

## interior space

- 29.7 ft<sup>3</sup> (0.8 m<sup>3</sup>) with shelf area of 10.8 ft<sup>2</sup> (1 m<sup>2</sup>) provided on two tiers

## shelving

- Two tiers of white epoxy coated steel wire shelving (each shelf is 28.8"W x 27"D [73 cm x 68.6 cm])
- Each shelf is supported by shelf clips allowing ½" vertical adjustments
- Maximum growing height is 22.6" (57.5 cm)

## refrigeration

- Top mounted air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and tight temperature control. Continuous running condensing unit ensures precise temperature control by alternately cycling refrigerant and hot gas to coil; also prolongs compressor life, and eliminates risk of ice build up in coil.
- Extended stem solenoid valves for quiet and long life operation
- Ceiling mounted evaporator coil incorporates twin air circulation fans in aluminum housing (heat rejection to ambient [standard chamber] = 2,674 BTU/hr.)

## temperature range

- 7°-44°C (±0.5°C) lights on and 2°-44°C (±0.5°C) lights off

## temperature safety limit controls

- (Experiment Protection) Adjustable high and low temperature controls, audible alarms, and visual indicators provided
- Controls shut down all power to the chamber, activating alarms
- System automatically resets when temperature returns to normal range

## humidity control (optional)

- Ultrasonic Humidifier with Advanced RH Sensor (H11)
- Ultrasonic Humidifier and Dehumidifier with Advanced RH Sensor (H12)
- Ultrasonic Humidifier with Electronic RH sensor (H14)
- Ultrasonic Humidifier and Dehumidifier with Electronic RH sensor (H15)

*See other specification sheets or consult factory for additional information.*

## options (most popular)

- IntellusUltra Connect (C9)
- Additive CO<sub>2</sub> control
- CO<sub>2</sub> removal system
- Self-contained water-cooled condensing unit
- Dry alarm contacts
- Closed loop dimmable lighting with PAR light sensor (Q22)
- Open loop dimmable lighting per tier (Q23<sup>+</sup>)
- Extended temperature ranges available
- Convenience receptacles

*Contact [info@percival-scientific.com](mailto:info@percival-scientific.com) with questions or for additional information.*

## electrical service requirements

- 120/1/60 - two grounded cords each with NEMA 5-15P plug provided for standard chamber
- Cord #1 RLA=6.2 & cord #2 RLA=5.4 (combined MCA=14.5)

## regulatory standards

- Electrical Safety: UL-508A, certified and labelled by Percival Scientific under UL file number E340161
- Quality System: ISO 9001:2015, certified under DQS, Inc. under certification number 10017261

## helping you create better science

Percival Scientific controlled environment systems are the culmination of over 60 years of design and manufacturing experience. Our high quality products have been developed through direct partnerships with the scientific community and offer platforms that are highly customizable and provide superior performance. We understand that scientific innovation is bred through creativity, passion, technical expertise and attention to detail, and we are proud to help you create better science.



Percival Scientific, Inc.

505 Research Drive • Perry, IA 50220 USA

800.695.2743 • 515.465.9363 • Fax: 515.465.9464

[www.percival-scientific.com](http://www.percival-scientific.com)