

Spectro UV-VIS Double Beam PC Scanning Spectrophotometer



Special Offer*

\$6900

Model LBMUVD2960

Spectra UV-Vis Double PC (Model LBMUVD-2960) is a high-performance UV-Vis double beam automatic-scanning spectrophotometer. It is a two (2) cell spectrophotometer with a variable bandwidth of 0.5, 1.0, 2.0 and 5.0 nm. Model LBMUVD-2960 spectrophotometer offers high performance, ease of use and reliability, which can be used in various applications. Spectrophotometer Model LBMUVD-2960 can be used extensively for qualitative and quantitative analysis in such fields as pharmaceutical inspection, clinical analysis, petro-chemistry laboratories, chemistry and biochemistry laboratories, DNA/RNA analysis as well as inequality control departments, i.e. environmental control, water management food processing, and agriculture. Spectro UV-Vis Double PC utilizes a new optical system design and is microcomputer controlled. With its focused-beam design, the system provides optimal and reproducible results for small samples. The sample beam and the reference beam are provided within the same sampling space which in turn facilitates wider and longer scan of data providing a more detailed view of the results in an easy-to-use environment. This instrument has excellent baseline stability and high-resolution and permits scanning, quantitative analysis, kinetic spectrophotometric analysis and DNA/RNA analysis through PC control. This product is capable of processing data, from analytical and spectrum testing.

Spectro UV-Vis Double PC (Model UVD-2960) has a large LCD screen which displays the menu screen and of course makes the device user-friendly. Additionally, this instrument has powerful built-in software which permits the apparatus to be linked to a computer and a printer to display the photometric and spectral data on the PC monitor.

Spectro UV-Vis Double PC with variable band-Width of 0.5, 1.0, 2.0 and 5.0nm is a high-performance, reliable, and exceptional value Instrument which is the hallmark of this UV-Vis spectrophotometer.

OUR NEW SOFTWARE UV-WIS 6.0 WITH 30 SPECTRA can be used with Windows XP, Windows 7 and Windows 8. It is capable of testing more applications with its RS-232 and USS connections, and supports the data export of measured results to the PC and then flash drive, when additional data storage is required. One of the new features is that it provides 3-D graphing of the spectral results.

Features:

- **Baseline Stability:** The Double beam monitoring ratio system enhances baseline stability.
- **Excellent Resolution:** The big-caliber light path enhances the instrument's energy, reduces its noise and raises its resolution performance
- **2 Cell Holder:** Spectro UVD-2960 has 2 cell holder for reference (standard) and sample.
- **User-friendly light source:** The socket deuterium lamps and tungsten lamps facilitate light source replacement, simplify maintenance and reduce operation error.
- **Convenient Display:** The large backlit LCD screen displays both photometric values and spectral curves.
- **Full use of Computer Technology:** Being computer controlled with RS-232 and USB interface and working on the Windows platform with the UV/Win application software.
- **The key components adopt all from the world famous manufacturer,** such as deuterium lamp, silicon photodiode and holographic grating, which ensures the stabilization and credibility of the Instrument for extended life.
- **Computer System is optional (NOT INCLUDED).**

Accessories:

2 Fixed Cell Holder (one reference and one sample)	1 Power cable	1 Block Light Cell
8 Optical Glass Cells 10mm	1 PC cable	1 Extra fuse
2 Quartz Cells 10mm	1 Software CD for Windows 98/2000/XP	
1 Dust cover	1 Software Operation Manual	
1 Instruction manual	1 Spare Tungsten Halogen Lamp	

EMAIL: diamed@diamed.ca

Diamed 

Software Specifications:

Monoprocessor Built-in Application:

Photometric Measurement: Measuring transmittance or absorbance at the current wavelength together with K factor calculations.

Spectrum Scan: Carrying out scanning of transmittance or absorbance on the selected wavelength range together with peak-pick module.

Quantitative Determination: Regression of standard curves and direct determination concentration of samples

New UVWin 6.0 PC Windows Application Software (RS-232 and USB Interface) to link Spectro to computer and printer:

Photometric Measurement: Measuring the photometric values at 1-10 wavelengths together with mathematical calculations according to entered quotations. Spectrum Scan: Producing Wavelength scans within the operating parameters on samples together with powerful data holding facilities.

Quantitative Determination: Determination of unknown concentration with methods of 1-3 wavelength quantitation, together with fitting of calibration curve of 1st ~ 4th order.

Kinetics: Recording curves of changing photometric values of samples against timecourse at the selected wavelengths together with powerful data handling facilities

Output: With the Windows clipboard, the measured data and graphics can be copied to other applications software for reports.

Technical Specifications:

Wavelength Range:	190 nm – 1100 nm	Baseline Stability:	0.0008Abs/h (2 hours warming up, 2nm Bandwidth, 500nm)
Spectral Bandwidth:	0.5, 1.0, 2.0 and 5.0 nm	Slew Rate of Wavelength:	3600nm/min
Resolution:	0.1nm	DNA/RNA Measurement:	Results Printout: Printing of measured data by using any Printer with Parallel Port connection available.
Straylight:	>2.10Abs (200nm)	Mainframe:	Compact and standalone spectrophotometer mainframe
Wavelength Accuracy:	±0.3 nm (with automatic wavelength correction).	Light Source:	Socket Deuterium Lamp and Socket Tungsten Halogen Lamp
Wavelength Reproducibility:	±0.2 nm	Detector:	Double Beam
Photometric System:	Double beam optical system	Sample Chamber:	2 cell holder
Photometric Method:	Transmittance, absorbance, energy, concentration	Display:	Liquid Crystal Display (LCD 320/240 dot matrix)
Photometric Range:	-0.3~3.0 Abs (0~200%T)	Keypad:	Touch soft keys.
Photometric Accuracy:	±0.002Abs (0~0.5A) , ±0.004Abs (0.5~1.0A), ±0.3%T (0~100%T)	PC Interface:	PC Interface: RS-232, USB
Photometric Reproducibility:	±0.001Abs (0~0.5 A), ±0.002Abs (0.5~1.0A), ±0.15%T (0~100%T),	Size:	22"x16"x10"
Photometric Display:	-9999 ---- 9999	Weight:	55 Lb
Photometric Noise:	±0.001Abs (at 500nm, 2nm Spectral Bandwidth 0 Abs)		
Scanning Speed:	1400nm/min		
Baseline Flatness:	±0.0015Abs (2000 nm. ~ 1100 nm.)		
Voltage:	110V-240V		



Special Offer*
\$6900
Model LBMUVD2960

Contact your Territory Manager for More Details

**Limited Time Offer*

Diamed^{ca}

TOLL FREE 1.800.434.2633
LOCAL 905.625.6021
WEBSITE www.diamed.ca

FAX 1.800.293.2987
FAX 905.625.6280
EMAIL diamed@diamed.ca



PO#

UVD-2960-Aug2016